

## Features

- Ultra High Efficiency (Up to 92.0%)
- Five Channels Output
- Active Power Factor Correction (0.99 Typical)
- Constant Current Output
- Lightning Protection
- All-Around Protection: SCP, OTP, OVP
- Waterproof (IP67) and UL Dry / Damp / Wet Location
- Class 2 Output
- 5 years warranty



## Description

The EUC-180PxxxDT(ST) series is a 180W, five-channel, constant-current LED driver that operates from 90-305 Vac input with excellent power factor. It is created for flood, tunnel and street lights. The high efficiency of these drivers and compact metal case enables them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, output over voltage, short circuit, and over temperature.

## Models

Output Current (1)	Input Voltage Range	Output Voltage Range	Max. Output Power	Typical Efficiency (2)	Power Factor		Model Number
					120Vac	220Vac	
700 mA	90 ~ 305 Vac	29~54 Vdc	189 W	92.0%	0.99	0.94	EUC-180P070DT(ST) <sup>(3)</sup>
1050 mA	90 ~ 305 Vac	19~36 Vdc	189 W	90.0%	0.99	0.94	EUC-180P105DT(ST) <sup>(4)</sup>
1400 mA	90 ~ 305 Vac	14~25 Vdc	175 W	90.0%	0.99	0.94	EUC-180P140DT(ST) <sup>(5)</sup>

- Notes:** (1) The output current is adjustable at factory from 50% to 100%.  
 (2) Measured at full load and 220 Vac input.  
 (3) Class 2 output (USR), Non-Class 2 output (CNR).  
 (4) Class 2 output (USR), Class 2 output (CNR) for wet location.  
 (5) Class 2 output (USR & CNR) for wet location.

## Input Specifications

Parameter	Min.	Typ.	Max.	Notes
Input Voltage	90 V	-	305 V	
Input Frequency	47 Hz	-	63 Hz	
Leakage Current	-	-	1 mA	At 277Vac 60Hz input
Input AC Current	-	-	2.5 A	Measured at full load and 100 Vac input.
	-	-	1.1 A	Measured at full load and 220 Vac input.
Inrush Current	-	-	65 A	At 220Vac input, 25°C cold start, duration=0.6 ms, 10%Ipk-10%Ipk.
Inrush Current(I <sup>2</sup> t)	-	-	0.3 A <sup>2</sup> s	
PF	0.90	-	-	At 100-277Vac, 50-60Hz, 75%-100%load
THD	-	-	20%	

## Output Specifications

Parameter	Min.	Typ.	Max.	Notes
Output channel	-	5	-	
Output Current Tolerance	-5%	-	5%	
No-load Output Voltage I <sub>o</sub> =700 mA I <sub>o</sub> =1050 mA I <sub>o</sub> =1400 mA	- - -	- - -	62V 42V 32V	Hiccup mode.
Output Current Ripple (pk-pk)	-	10% I <sub>o</sub>	15% I <sub>o</sub>	
Output Overshoot / Undershoot	-	-	10%	When power on or off.
Line Regulation	-	-	±1%	
Load Regulation	-	-	±3%	
Turn-on Delay Time	-	1.0 s	2.0 s	Measured at 120Vac input, 75%-100%load
	-	0.5 s	1.5 s	Measured at 220Vac input, 75%-100%load
Temperature Coefficient	-	0.03%/°C	-	Case temperature = 0°C ~T <sub>c</sub> max

**Note:** All specifications are typical at 25 °C unless otherwise stated.

## Protection Functions

Parameter	Min.	Typ.	Max.	Notes
Over Temperature Protection	-	110 °C	-	When OTP occurs, the output current decreases down to the half of the normal output current. The output shall be auto recovery when case temperature becomes normal.
Short Circuit Protection	No damage shall occur when any output operating in a short circuit condition. The power supply shall be self-recovery when the fault condition is removed.			

## General Specifications

Parameter	Min.	Typ.	Max.	Notes
Efficiency I <sub>o</sub> =700 mA I <sub>o</sub> =1050 mA I <sub>o</sub> =1400 mA	88.0% 85.5% 85.5%	89.0% 86.5% 86.5%	- - -	Measured at full load, 120Vac input, 25°C ambient temperature, after the unit is thermally stabilized. It will be about 1% lower, if measured immediately after startup.
Efficiency I <sub>o</sub> =700 mA I <sub>o</sub> =1050 mA I <sub>o</sub> =1400 mA	91.0% 89.0% 89.0%	92.0% 90.0% 90.0%	- - -	Measured at full load, 220Vac input, 25°C ambient temperature, after the unit is thermally stabilized. It will be about 1% lower, if measured immediately after startup.
Efficiency I <sub>o</sub> =700 mA I <sub>o</sub> =1050 mA I <sub>o</sub> =1400 mA	91.0% 89.0% 89.0%	92.0% 90.0% 90.0%	- - -	Measured at full load, 277Vac input, 25°C ambient temperature, after the unit is thermally stabilized. It will be about 1% lower, if measured immediately after startup.
MTBF	-	326,000 Hours	-	Measured at 220Vac input, 80%Load and 25°C ambient temperature (MIL-HDBK-217F)

## General Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Lifetime	-	101,000 Hours	-	Measured at 220Vac input, 80%Load; Case temperature=60°C @ Tc point. See lifetime vs. Tc curve for the details
Operating Case Temperature for Safety Tc_s	-40°C		90 °C	
Operating Case Temperature for Warranty Tc_w	-40°C		+70 °C	Case temperature for 5 years warranty
Storage Temperature	-40°C	-	+85 °C	Humidity: 5% RH to 100% RH
Dimensions Inches (L x W x H) Millimeters (L x W x H)		8.41 x 3.2 x 1.5 213.5 x 82 x 38		With mounting ear 9.47 x 3.2 x 1.5 240.5 x 82 x 38
Net Weight	-	1340 g	-	

**Note:** All specifications are typical at 25 °C unless otherwise stated.


## Safety & EMC Compliance

Safety Category	Standard
UL/CUL	UL8750, UL1012, UL1310 Class 2, CSA-C22.2 No. 107.1, CSA C22.2 NO. 223-M91 Class 2
CE	EN 61347-1, EN61347-2-13
KS	KS C 7655
EMI Standards	Notes
EN 55015	Conducted emission Test & Radiated emission Test
EN 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
FCC Part 15	ANSI C63.4 Class B This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired Operation.
EMS Standards	Notes
EN 61000-4-2	Electrostatic Discharge (ESD): 15 kV air discharge, 8 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: line to line 4 kV, line to earth 6 kV
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test



## Safety & EMC Compliance (Continued)


EMS Standards	Notes
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment

## Lifetime vs. Case Temperature Curve




## Efficiency vs. Load






### Power Factor Characteristics






### Total Harmonics Distortion



## Dimming Control (On secondary side)


Parameter	Min.	Typ.	Max.	Notes
12V output voltage (Vaux)	10.8 V	12 V	13.2 V	
12V Output source current	0 mA	-	20 mA	
Absolute Maximum voltage on the 1~10V input pin	0 V	-	12 V	
Source current on 1~10V input pin	0 uA	-	200 uA	

The dimmer control may be operated from either a potentiometer or from an input signal of 1 – 10 Vdc. Two recommended implementations are provided below.





EUC-180PxxxST



## RoHS Compliance

Our products comply with the European Directive 2011/65/EC, calling for the elimination of lead and other hazardous substances from electronic products.

DISCONTINUED



## Revision History

Change Date	Rev.	Description of Change		
		Item	From	To
2013-06-03	A	Datasheets Release	/	/
2013-10-10	B	No-load Output Voltage	/	Updated
2017-12-22	C	KS	/	Added
		Features	/	Updated
		Description	/	Updated
		Models	Notes	Updated
		Input Specifications	PF/THD	Updated
		Output Specifications	Turn-on Delay Time	Updated
		Output Specifications	Temperature Coefficient	Updated
		General Specifications	Case Temperature	Operating Case Temperature for Safety Tc_s
		General Specifications	Operating Case Temperature for Warranty Tc_w	Added
		General Specifications	Storage Temperature	Added
		General Specifications	With mounting ear	Added
		Environmental Specifications	/	Deleted
		Safety & EMC Compliance	/	Updated
		Derating Curve	/	Updated
Mechanical Outline	/	Updated		