

Features

- High Efficiency up to 93.0%
- Constant Output Voltage
- No Load Power Consumption < 0.5 W
- Excellent Thermal Performance up to 50°C Ambient Temperature
- Input Surge Protection: DM 4 kV
- All-Around Protection: OCP, OVP, OTP, SCP
- Class II
- SELV Output
- 5 Years Warranty



Description

The LUV-100SxxxSF is a 100W, constant-voltage LED driver that operates from 90-305 Vac input with excellent power factor. It is created for many lighting applications including architectural, decorative and signage. The high efficiency of the driver enables them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, over current, output over voltage, over temperature, and short circuit.

Models

Output Voltage (V)	Output Current Range (A)	Max. Output Power (W)	Typical Efficiency ⁽¹⁾	Model Number ⁽²⁾⁽³⁾
12	0-8.34	100	92.0%	LUV-100S012SF
24	0-4.17	100	91.5%	LUV-100S024SF
36	0-2.78	100	92.0%	LUV-100S036SF
48	0-2.09	100	93.0%	LUV-100S048SF

- Notes:** (1) Measured at 100% load and 220Vac input (see below “General Specifications” for details).
 (2) Certified input voltage range: UL, FCC 100-277Vac; otherwise 100-240Vac.
 (3) SELV output.

Input Specifications

Parameter	Min.	Typ.	Max.	Notes
Input AC Voltage	90 Vac	-	305 Vac	
Input DC Voltage	127 Vdc	-	300 Vdc	
Input Frequency	47 Hz	-	63 Hz	
Input AC Current	-	-	1.03 A	Measured at 100% load and 120Vac input.
	-	-	0.55 A	Measured at 100% load and 220Vac input.
Inrush Current(I ² t)	-	-	2.89 A ² s	At 220Vac input, 25°C cold start, duration=336 μs, 10%I _{pk} -10%I _{pk} .
PF	0.9	-	-	At 100-277Vac, 50-60Hz, 60%-100% Load (60-100W)
THD	-	-	20%	
PF	0.95	-	-	At 220Vac, 50Hz, 100% Load (100W)
THD	-	-	10%	At 220-240Vac, 50-60Hz, 60%-100% Load (60-100W)

Output Specifications

Parameter	Min.	Typ.	Max.	Notes
Output Voltage Tolerance	-5%Vo	-	5%Vo	At 100% load condition
Total Output Voltage Ripple (pk-pk)	-	-	2%Vo	At 100% load condition. Measured by 20 MHz bandwidth oscilloscope and the output paralleled a 0.1 uF ceramic capacitor and a 10 uF electrolytic capacitor.
Startup Overshoot / Undershoot	-	-	5%Vo	At 100% load condition
Line Regulation	-	-	±1 %	Measured at 100% load
Load Regulation	-	-	±2 %	
Turn-on Delay Time	-	-	0.5 s	Measured at 120Vac input, 100%Load
	-	-	0.5 s	Measured at 220Vac input, 100%Load
Hold up Time	20 ms	-	-	Measured at 230Vac input, 100%Load
Load Dynamic Response	Output Deviation	-	5%Vo	R/S: 1 A/μs Load: 25% ~ 100% load
	Settling Time	-	10 ms	
Temperature Coefficient of Vo	-	0.03%/°C	-	Case temperature = 0°C~Tc max

General Specifications

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 120 Vac input: LUV-100S012SF LUV-100S024SF LUV-100S036SF LUV-100S048SF	88.5% 88.0% 89.0% 89.0%	90.5% 90.0% 91.0% 91.0%	- - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
Efficiency at 220Vac input: LUV-100S012SF LUV-100S024SF LUV-100S036SF LUV-100S048SF	90.0% 89.5% 90.0% 91.0%	92.0% 91.5% 92.0% 93.0%	- - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
Efficiency at 277Vac input: LUV-100S012SF LUV-100S024SF LUV-100S036SF LUV-100S048SF	90.5% 90.0% 90.5% 91.0%	92.5% 92.0% 92.5% 93.0%	- - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
No Load Power	-	-	0.5 W	Measured at 230Vac
MTBF	-	523,000 Hours	-	Measured at 220Vac input, 80%load and 25°C ambient temperature (MIL-HDBK-217F)
Lifetime	-	120,000 Hours	-	Measured at 220Vac input, 80%load and 70°C case temperature. See lifetime vs. Tc curve for the details
Operating Case Temperature for Safety Tc_s	-40 °C	-	+90 °C	
Operating Case Temperature for Warranty Tc_w	-40 °C	-	+70 °C	Case temperature for 5 years warranty Humidity: 10%RH to 90%RH; No condensation
Storage Temperature	-40 °C	-	+85 °C	Humidity: 5%RH to 95%RH; No condensation
Dimensions Inches (L × W × H) Millimeters ((L × W × H)	6.34 x 2.30 x 1.48 161 x 58.5 x 37.5			
Net Weight	-	600 g	-	


Safety & EMC Compliance

Safety Category	Standard
UL/CUL	UL 8750, CAN/CSA-C22.2 No. 250.13
ENEC & CE	EN 61347-1 ⁽¹⁾ , EN 61347-2-13
CB	IEC 61347-1 ⁽¹⁾ , IEC 61347-2-13
CCC	GB 19510.1, GB 19510.14
KS	KS C 7655
SAA	AS/NZS 61347.1, AS/NZS 61347.2.13
Performance	Standard
ENEC	EN IEC 62384
EMI Standards	Notes
EN IEC 55015/GB/T 17743 ⁽²⁾	Conducted emission Test & Radiated emission Test
EN IEC 61000-3-2/GB 17625.1	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
FCC Part 15 ⁽²⁾	ANSI C63.4 Class B
	This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired operation.
EMS Standards	Notes
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: Differential Mode 4 kV
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment


Notes: (1) This product meets the requirements for EN/BS EN/IEC 61347-1 [Annex O (Double insulation)].

(2) This LED driver meets the EMI specifications above, but EMI performance of a luminaire that contains it depends also on the other devices connected to the driver and on the fixture itself.


Derating



Lifetime vs. Ambient Temperature





Inrush Current Waveform





Input AC Voltage	I_{peak}	t_{width} (@ 50% I_{peak})
120Vac	51.0A	132 μ s
220Vac	107A	128 μ s
277Vac	127A	132 μ s


MCB	Tripping Curves	B	B	B	B	C	C	C	C
	Rated Current	10A	16A	20A	25A	10A	16A	20A	25A
The Number of LED Driver can be Configured	120	6	10	12	16	7	12	15	18
	220	7	11	14	17	11	19	23	29
	277	5	8	10	12	8	13	17	21

Efficiency vs. Load






Power Factor



Total Harmonic Distortion




Protection Functions


Parameter	Notes
Over Current Protection	Auto Recovery. The driver shall be self-recovery when the fault condition is removed.
Over Temperature Protection	Auto Recovery. Returning to normal after over temperature is removed.
Short Circuit Protection	Auto Recovery. No damage will occur when any output is short circuited. The output shall return to normal when the fault condition is removed.
Over Voltage Protection	Limits output voltage at no load and in case the normal voltage limit fails.

Mechanical Outline

LUV-100S012SF



LUV-100S024SF/LUV-100S036SF/LUV-100S048SF



RoHS Compliance

Our products comply with reference to RoHS Directive (EU) 2015/863 amending 2011/65/EU, calling for the elimination of lead and other hazardous substances from electronic products.

Revision History

Change Date	Rev.	Description of Change		
		Item	From	To
2023-09-07	A	Datasheet Release	/	/
2023-10-08	B	Efficiency vs. Load	/	Updated
2024-11-04	C	Product Photograph	/	Updated
		UKCA logo	/	Deleted
		Input Specifications	/	Updated
		Safety & EMC Compliance	/	Updated
		Inrush Current Waveform	/	Updated
		Mechanical Outline	/	Updated